

Fujitsu recommends Windows 8 Pro.

# Data Sheet

## Fujitsu ESPRIMO Q510 Desktop PC

The Mini with More PC per cm<sup>3</sup>

A real eye-catcher on your desk and anywhere else. The extremely small and elegant Fujitsu ESPRIMO Q510. The mini PC combines the performance of a fully equipped Desktop PC, low energy consumption, ENERGY STAR® certification, hardly any noise, a large number of practical connections, such as HDMI and USB 2.0 - all on a very small footprint with a volume of only 1.9 liters

### An elegant mini PC for challenging office tasks

Eye-catcher on every desk with a modern and exclusive design

- Fully equipped PC with a volume of only 1.9 liters - based on standard desktop technology

### Black shell and a green core

Needs only 9.2 watts in idle-mode and saves valuable resources

- Sophisticated technology, low energy-consuming processors and an up 90 % effective onboard power supply

### Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and function tests - all under one roof in Germany

### Superb usability



Pleasant working environment due to a tidy desk

- Horizontal or vertical operations and an integrated VESA mount, service door for easy upgrade of major components

### Advanced technology

Get your office job done fast and reliable

- 3rd generation Intel® Core™ processor family



# Components

<b>Processor</b>	Intel® Core™ i5-3470T processor (2 Cores / 4 Threads, 2.90 GHz, up to 3.6 GHz, 3 MB, Intel® HD Graphics 2500) * Intel® Core™ i3-3220T processor (2 Cores / 4 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics 2500) Intel® Pentium® processor G2020T (2 Cores / 2 Threads, 2.50 GHz, 3 MB, Intel® HD Graphics) Intel® Celeron® processor G1610T (2 Cores / 2 Threads, 2.30 GHz, 2 MB, Intel® HD Graphics) *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
<b>Operating systems</b>	
<b>Operating system</b>	Windows 8 Pro Windows 8 Windows® 7 Professional 64-bit Windows® 7 Professional 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Home Basic (EM) 32-bit
<b>Operating system compatible</b>	Windows® XP
<b>Operating system notes</b>	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a>
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM 4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM 8 GB (1 module(s) 8 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM
<b>Hard disk drives (internal)</b>	SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch, SED SSD SATA III, 128 GB, 2.5-inch HDD SATA II, 7200 rpm, 320 GB, 2.5-inch HDD SATA II, 5400 rpm, 1000 GB, 2.5-inch* HDD SATA II, 5400 rpm, 750 GB, 2.5-inch* HDD SATA II, 5400 rpm, 500 GB, 2.5-inch* HDD SATA II, 5400 rpm, 320 GB, 2.5-inch* HDD SATA II, 5400 rpm, 250 GB, 2.5-inch*
<b>Hard disk notes</b>	*Disk imaging software of the customer must be 4k sector size / advanced format ready Up to 20 GB of HDD space is reserved for system recovery
<b>Drives (optional)</b>	BD Triple Writer SATA Slot-in slim DVD Super Multi Slot-in slim
<b>Interface add on cards/components (optional)</b>	WLAN 802.11 b/g/n (2x2) and Bluetooth (dedicated regions only)
<b>Base unit</b>	ESPRIMO Q510
<b>Mainboard</b>	
<b>Mainboard type</b>	D3173
<b>Formfactor</b>	proprietary
<b>Chipset</b>	Intel® H61
<b>Processor socket</b>	LGA 1155
<b>Processor quantity maximum</b>	1
<b>Memory slots</b>	2 SO DIMM (DDR3, 1333 MHz)
<b>Supported capacity RAM (max.)</b>	16 GB
<b>Memory frequency</b>	1333 MHz
<b>Memory notes</b>	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same

**Mainboard**

LAN	10/100/1000 MBit/s Intel® 82579 V
Integrated WLAN	1 (optional)
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	High Definition audio, 5.1 surround sound, Buzzer

**I/O controller on board**

Serial ATA total	2
Controller functions	Serial ATA II (3 Gbit) NCQ AHCI

**Interfaces**

Audio: line-out / headphone	1
Audio: line-in / microphone	1
USB 2.0 total	6
USB front	2x 2.0
USB rear	4x 2.0
VGA	1 (via DVI to VGA adapter, part of shipment)
DVI	1 (DVI-I)
HDMI	1
Ethernet (RJ-45)	1
Kensington Lock support	1
Multicardreader	1
Interface Module notes	Anytime USB charge functionality

**Input device / components**

	Optical USB wheel mouse
Input devices (optional)	KBPC PX ECO Mouse M440 ECO

**Drive bays**

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim slot-in

**Graphics on board**

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500 (depending on processor)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel

**Graphics on board**

<b>TFT resolution (HDMI)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
<b>Graphics features</b>	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.3 (depending on CPU) Open CL™ 1.1 (depending on CPU)
<b>Graphics notes</b>	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 115V/230V; 10% / 20% / 50% / 100% load) : 83% / 87% / 90% / 88%
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	65 W (integrated in system)
<b>Power factor correction/active power</b>	No (meets input harmonic current according EN61000-3-2)
<b>Monitor outlet</b>	No

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
<b>Link to Energy White Paper</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=a95609a6-cda7-45f8-a45d-97b0976f4ed2">http://docs.ts.fujitsu.com/dl.aspx?id=a95609a6-cda7-45f8-a45d-97b0976f4ed2</a>

**Heat dissipation**

<b>Heat dissipation notes</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise emission**

<b>Related Processors for noise</b>	Intel® Core i3-2120T
<b>Standard noise emission</b>	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
<b>Standard noise notes / description</b>	A weighted sound power level Lw <sub>ad</sub> (in B) / Workplace related A-weighted sound pressure level Lp <sub>Am</sub> (in dB(A))
<b>Standard noise operation mode: HDD load</b>	3.3 B / 19 dB(A)
<b>Standard noise operation mode: Idle mode</b>	3.3 B / 19 dB(A)
<b>Standard noise operation mode: ODD load</b>	4.7 B / 33 dB(A)
<b>Standard noise operation mode: Office applications 2.0</b>	3.2 B / 18 dB(A)
<b>Blue angel noise emission according certification</b>	According to ISO 7779:2010, ECMA-74 for max. possible configuration
<b>Blue angel noise notes / description</b>	A weighted sound power level Lw <sub>ad</sub> (in B); 1B = 10dB
<b>Blue angel noise operation mode: HDD load</b>	3.3 B = 33 dB
<b>Blue angel noise operation mode: Idle mode</b>	3.2 B = 32 dB
<b>Blue angel noise operation mode: ODD load</b>	4.7 B = 47 dB

**Dimensions / Weight / Environmental**

<b>Dimensions (W x D x H)</b>	185 x 188 x 54 mm
	7.29 x 7.41 x 2.13 inch
<b>Operating position</b>	Vertical / horizontal (no feet needed)
<b>VESA mount</b>	integrated (100mm), applicable for selected monitors only, additional mounting kit for specific monitors optional
<b>Weight</b>	1.6 kg
<b>Weight (lbs)</b>	3.53 lbs
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Operating ambient temperature</b>	10 - 35 °C (50 - 95 °F)

**Compliance**

<b>Product</b>	ESPRIMO Q510
<b>Model</b>	MPC2
<b>Germany</b>	TÜV GS Blauer Engel / Blue Angel
<b>Europe</b>	CE Nordic Swan
<b>USA/Canada</b>	FCC Class B cCSAus
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 (dedicated regions) EPEAT® Gold (dedicated regions)
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates/">https://sp.ts.fujitsu.com/sites/certificates/</a>

**Additional Software**

<b>Additional software (preinstalled)</b>	Adobe® Reader® Anti Virus software (60 days trial version) Win7: Fujitsu Recovery (Hard Disk Based Recovery) Win8: Microsoft Push Button Recovery (Hard Disk Based Recovery) Don't forget Office.
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD (BD/DVD playback software for Blu-ray Disc™) CyberLink PowerDVD (DVD playback software) Nero Essentials XL

**Compatibility (references)**

	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
--	--

**Manageability**

<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
---------------------------------	--

**Security**

<b>System protection</b>	Kensington Lock support Housing Lock Plate (to use with Kensington lock)
<b>Audit proof protection</b>	Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces External USB ports can be disabled separately

<b>Security</b>	
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader
<b>Packaging information</b>	
Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	48
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	If keyboard is included in packaging: 1.) packaging dimension is increasing to: 500 x 208 x 290mm / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 49; printed user documentation is bleached in chlorine free process;
<b>Warranty</b>	
Standard Warranty	1 year
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Maintenance and Support Services - the perfect extension</b>	
Recommended Service	9x5, Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>



## Recommended Accessories

### USB-Port Replicator PR07



This Port Replicator is the perfect docking solution for notebooks without a docking connector. Turn your notebook into a desktop complete with two screens for a real productivity boost thanks to the DualView feature. Plus connect to the local area network and to all of your peripherals with a single USB plug.

Order Code:  
S26391-F6007-L300

### Display B22W-6 LED proGREEN



The B22W-6 LED proGREEN offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Order Code:  
S26361-K1392-V160

**Display B24W-6 LED**

The Fujitsu Display B24W-6 LED combines the best ergonomic and energy saving solutions for intensive office use. The flexible stand with height adjust assures an individual and healthy posture for long-time working sessions. With its impressive screen size it allows working on different documents in parallel or standard CAD applications.

Order Code:  
S26361-K1427-V140

**CELVIN® Drive M200**

The CELVIN Drive M200 is an ultra-portable and high-class storage device. Since it is compatible with USB3.0 and USB 2.0, it can be used with a large variety of devices. It is ideal for notebook and desktop users. It makes data backup easier and faster than ever.

Order Code:  
S26341-F103-L500

**SOUNDSYSTEM DS E2000 Air**

The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:  
S26391-F7128-L600

**Keyboard KB900**

The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4\*\* (\*\*:  
Country specific variation)

**Wireless Keyboard Set LX900**

The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K564-L4\*\* (\*\*:  
Country specific variation)

# More information

## Fujitsu OPTIMIZATION Services

In addition to Fujitsu ESPRIMO Q510, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about Fujitsu ESPRIMO Q510, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

Copyright © Fujitsu Technology Solutions

## Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

FUJITSU Technology Solutions  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2013-02-27 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
Copyright © Fujitsu Technology Solutions